



# TEC-GUARD

# EXTREME

## TEC-GUARD EXTREME HEAVY-DUTY MOTOR OIL



**TEC-GUARD® Extreme TO-4 Fluids** are heavy duty lubricants formulated for use in transmission and final drives requiring Caterpillar TO-4 or Allison C-4 fluids. MPT Torque TO-4 Fluids can also be used in wet brakes I hydrostatic transmissions, torque converters, and hydraulic systems calling for TO-4 or C-4 Fluids. They are formulated to work in both newly developed and older design drive train components. .

**TEC-GUARD® Extreme TO-4 Fluids** meets or exceeds the following performance requirements and industry specifications/applications: CAT TO-4. Allison C-4, ZF TE-ML 03C/07F, API GL-3, Komatsu-Dresser, Eaton Fuller Transmissions, Dana/Spicer Transmissions, Rockwell Transmissions, Euclid Equipment, Vickers M-2950S/35VQ25. Always consult your owner's manual for specific recommendations.

- Multi-purpose lubricant designed for use in transmissions, final drives, wet brakes, and hydraulic systems
- Available in 3 viscosity grades (10W, 30, 50) to meet varied operating needs
- Excellent oxidation resistance and sludge control
- Provides anti wear performance and corrosion protection for gears, hydraulic and pump components

Property	Test Method ASTM-D	SAE Viscosity Grade		
		10W	30	50
API Gravity	1298	30.1	28.6	26.4
Viscosity cSt @ 40°C	D445	29.1	84.5	188.9
Viscosity cSt @ 100°C	D445	5.0	9.85	17.0
VI	2270	95	95	95
FLASH POINT, °C/°F	D92	210/410	227/440	229/445
POUR POINT, °C/°F	D97	-36/-33	-27/-17	-10/8