



EXTREME

TEC-GUARD EXTREME FULL SYNTHETIC Heavy Duty Motor Oil 0W/20

TEC-GUARD® Extreme Full Synthetic HD 0W-20 is specifically formulated to protect the efficient diesel power of American diesel pickups, vans, cars and SUVs, giving you the edge to keep your vehicle operating at peak performance. It delivers outstanding value and excellent protection for customers seeking an upgrade over conventional, synthetic-blend or competing synthetic diesel oils.

APPLICATIONS

Use in diesel pickups, vans, cars and SUVs that require any of the following specifications:

0W-20: GM dexosD

Not for use in applications that require an API CK-4, SP or earlier API specification.

Test Method	
Kinematic Viscosity: cSt @ 100°C (ASTM D445)	8.9
Kinematic Viscosity: cSt @ 400°C (ASTM D445)	46.4
Viscosity Index (ASTM D2270)	176
CCS Viscosity @ °C, cP (ASTM D5293)	5590 (-35)
Pour Point, °C (°F) (ASTM D97)	-48 (-54)
Four-Ball Wear Test (ASTM D4172), Scar, mm	0.48
NOACK Volatility, % weight loss (g.100g) (ASTM D5800)	10.0
Total Base Number (ASTM D2896)	7.1
High-Temperature/High-Shear Viscosity, cP (ASTM D5481)	2.78
Sulfated Ash Content, wt. %	0.80



- Outstanding Engine Protection
- Viscosity Control
- Excels in Extreme Temperatures
- Minimizes Oil Consumption