



# TEC-GUARD®

## ARMOR

TEC-GUARD SYNTHETIC BLEND PASSENGER CAR MOTOR OILS



**TEC-GUARD® Armor Synthetic Blend 10W-40** is a synthetic blend engine oil that offers excellent oxidation stability, increases your engine's fuel economy, protects against deposits at all temperatures and it is backward compatible with earlier API/ILSAC performance levels.

**TEC-GUARD® Armor Synthetic Blend 10W-40** meets or exceeds the following performance requirements and industry specifications:

ILSAC GF-6, ILSAC GF-5, ILSAC GF-4, ILSAC GF-3, API SN PLUS, API SN, GM® 6094M, CHRYSLER® MS-6395. Always consult your owner's manual for specific recommendations.

Test Method		Product Numbers
NOVACK Volatility	<15%	Bulk
ASTM D93 - Flash Point, °C	238	Drum
ASTM D97 - Pour Point, °C	-46	Pail
ASTM D445 - Viscosity @ 40° C, cST	103	Keg
ASTM D445 - Viscosity @ 100° C, cST	14.5	Tote
ASTM D2270 - Viscosity Index	145	4/1 Gallon
		2/2.5 Gallon
		12/1 Quart
		10425264810W40

- Extremely low volatility, providing extended drain protection
- Industry leading high temperature deposit control
- Superior cold-cranking capabilities
- Enhanced anti-wear, anti-foam, bearing corrosion and anti-rust protection