

TEC-GUARD

CHEMICAL

CALIBRATION FLUID

Product Description

Tec-Guard Chemical Calibration Fluid is specifically formulated for use as a calibrating fluid in fuel injector test benches and pop testers.

Product Benefits

- Meets the requirements of SAE j967d and ISO/DIS 4113
- Conforms to Caterpillar spec 1E 1084 (12/16/1998) CAT Part # 6V-6068
- Application section from CAT Calibration Fluid 1E 1084
- Formulated for use as a calibration fluid fuel injector test benches and pop testers

TYPICAL PHYSICAL PROPERTIES		VALUES
Appearance		Clear Light Yellow Liquid
Orod		Petroleum
Specific Gravity, 60°F (15.6°C)	ASTM D1298	0.820-0.830
Weight, lb/gal., 60°F (15.6°C)		
Flash Point, COC	ASTM D56	>167°F (75°)
Sediment Including Water	ASTM D2273	0.01% Volume max.
Copper Strip Corrosion		1b max.
Foaming, 75°F (24°C)	ASTM D892	
After 5 min blowing		50 ml max.
After 2 min settling		0 ml max.
Humidity Corrosion. 50 hrs. @ 120°F (49°C)	ASTM D1748	Pass, no rust
Distillation		5% volume @ 410°F (210°C)
		95% volume @ 680°F (260°C)

Note: Tec-Guard makes no warranty or representation either expressed or implied, including warranty of merchantability or fitness concerning this product except that it conforms to the chemical description on the label. All risks resulting from the use of this product are to be borne by the buyer at its sole expense. Neither Tec-Guard nor the seller shall be responsible in any manner for any personal injury or property damage, or other type of loss resulting from the handling, storage, or use of this product

TEC-GUARD

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • www.tec-guard.com