

SAFETY DATA SHEET**I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

TEC-GUARD
400 S 14th Ave
Eldridge, IA 52748

I. PHYSICAL DATA

PRODUCT NAME: **TEC-GUARD SEMI-FLUID H-540**
CHEMICAL NAME : Petroleum Hydrocarbon
FORMULA: Trade Secret

EMERGENCY PHONE: 1-800-424-9300

II. HAZARDOUS IDENTIFICATION

NFPA RATING (SCALE 0-4) Health = 1 Flammability = 1 Reactivity = 0

EMERGENCY OVERVIEW: Do not ingest. Do not inhale dust. Use adequate ventilation and wash after handling.

GHS CLASSIFICATION:**Health**

Acute Toxicity Oral: Cat. 5
Eye Irritation: Cat. 2B
Skin Irritation: Cat. 3

Environmental

Acute Aquatic Toxicity: Not established
Chronic Aquatic Toxicity: Not established

GHS LABEL ELEMENTS:

Symbol(s):



Signal Word
Warning

Hazard Statements

May be harmful if swallowed. Can cause damage to organs through prolonged or repeated exposure. May cause skin and eye irritation.

Precautionary Statements

Wear protective gloves/protective clothing/eye protection/face protection IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or you feel unwell: Call a doctor/physician.

III. COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENT: Trade Secret

CAS NUMBER:

Calcium salts	68783-96-0	5-10%
Severely Hydrotreated Heavy Naphthenic Petroleum Oi	64742-52-5	75%
Isobutene-Butene polymer	9003-29-6	10%
Heavy Resins	8052-42-4	1-10%

IV. FIRST AID MEASURES

EYE CONTACT: Wash eyes with water for at least 30 minutes. If irritation persists, get medical attention.

SKIN CONTACT: Wash affected area with soap and water for approximately 30 minutes

INHALATION: Remove exposed person to fresh air.

INGESTION: Do not induce vomiting. Get immediate medical attention.

V. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use carbon dioxide, foam, sand or sodium bicarbonate.

**SPECIAL FIRE
FIGHTING**

PROCEDURES: Avoid breathing vapors or dusts. Use self-contained breathing apparatus with full face piece and protective clothing.

**UNUSUAL FIRE
AND EXPLOSIVE**

HAZARDS: None known.**VI. ACCIDENTAL RELEASE MEASURES****IF MATERIAL IS RELEASED OR SPILLED:** Contain spill and transfer to suitable containers.

Stop leak if you can do it without risk.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. If material is too viscous for pumping scrape it up with shovels into suitable containers for recycle or disposal.**Large Spills:** Dike far ahead of spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.**VII. HANDLING AND STORAGE****STORAGE:** Observe all federal, state and local regulations when storing or disposing of this substance. Keep away from incompatible substances.

Use good engineering practices to establish good ventilation. Avoid contact with skin, eyes and clothing. Wear suitable protective equipment to protect from contact. Avoid breathing mist or vapors. Wash skin thoroughly after handling. Store in closed containers away from extreme heat, sparks, open flame or oxidizing materials.

VIII. EXPOSURE CONTROLS/ PERSONAL PROTECTION**EXPOSURE GUIDELINES:** Petroleum Oil TWA(mist) 5.0mg/m³**SKIN PROTECTION:** Wear appropriate protective gloves to prevent direct contact.**EYE PROTECTION:** Wear safety goggles to prevent eye contact with substance.**OTHER PROTECTIVE****EQUIPMENT:** Impervious apron if needed to avoid prolonged or repeated skin contact.**ENGINEERING****CONTROLS:** Good general ventilation and/or local exhaust ventilation at the point of generation is recommended.**PERSONAL PROTECTIVE EQUIPMENT (Pictograms):****IX. PHYSICAL AND CHEMICAL PROPERTIES**

SOLUBILITY IN WATER:	Insoluble		
SPECIFIC GRAVITY:	1.005 @20°C		
APPEARANCE:	Red Liquid		
ODOR:	Mild Petroleum		
VAPOR DENSITY:	>1		
FLASH POINT:	350°F		
FLAMMABLE LIMITS	LOWER:	N/A	UPPER: N/A

X. STABILITY AND REACTIVITY

STABILITY:	This product is stable at ambient temperatures.
CONDITIONS TO AVOID:	Extreme heat or cold.
INCOMPATIBILITY:	Avoid contact with strong acids and strong oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS:	Exposure to high temperatures, such as those associated with fires causes product decomposition, resulting in the release of carbon monoxide, carbon dioxide, and other decomposition products.
HAZARDOUS POLYMERIZATION:	Will not occur.

XI. TOXICOLOGY INFORMATION

EYE IRRITATION:	Can irritate eyes.
SKIN IRRITATION:	Can irritate skin. Prolonged or repeated contact may cause dermatitis.
CHRONIC:	No data available to indicate product or components present at greater than 1.0% are chronic health hazards.

XII. ECOLOGICAL INFORMATION

No information available.

XIII. DISPOSAL INFORMATION

WASTE DISPOSAL: Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state and local regulations.

XIV. TRANSPORTATION INFORMATION

No classifications currently assigned.

XV. REGULATORY INFORMATION**STATUS:**

US (TSCA): Y
CANADA (DSL): Y
EUROPE (EINECS/ELINCS): Y
AUSTRALIA (AICS): Y
CHINA (IESCS): Y
JAPAN (ENCS): Y
SOUTH KOREA (KECI): Y

Y= All ingredients are on the inventory or exempt from listing
N= One or more non-exempt ingredients are not on the inventory

SECTION 302 EXTREMELY HAZARDOUS CHEMICALS:

Component	CAS#	% by Wt.
None		

SECTION 313 TOXIC CHEMICALS:

Component	CAS#	% by Wt.
None		

SARA TITLE III:

ACUTE (IMMEDIATE HEALTH HAZARD): No
CHRONIC (DELAYED HEALTH HAZARD): No
SUDDEN PRESSURE RELEASE: No
FIRE HAZARD: No
REACTIVE HAZARD: No

CERCLA (Comprehensive Environment Response, Compensation and Liability Act):

There is no calculable reportable quantity (RQ) for this product.

CLEAN WATER ACT: Under section 311 (b) (4) of this act, contamination of surface waters by petroleum products must be reported immediately to the National Response Center.

XVI. OTHER INFORMATION**TSCA (TOXIC SUBSTANCE CONTROL ACT) STATUS:**

All components of this formula are included in the TSCA inventory. This product does not contain nor was manufactured with Class 1 or 11 ozone depleting chemicals, Section 611 of the Clean Air Act.

HEALTH HAZARD

4-Deadly
3- Extreme Danger
2- Hazardous
1-Slightly Hazardous
0-Normal Material

NFPA FIRE HAZARD

Flash Points
4-Below 73°F
3-Below 100°F
2-Above 100°F, Not
exceeding 200°F
1-Above 200°F
0-Will not burn

REACTIVITY

4-May detonate
3-Shock and heat
may detonate
2-Violent chemical change
1-Unstable if heated
0-Stable

Table 3.8 Acute Toxicity

Acute toxicity	Cat. 1	Cat. 2	Cat. 3	Cat. 4	Category 5
Oral (mg/kg)	≤ 5	> 5 ≤ 50	> 50 ≤ 300	> 300 ≤ 2000	Criteria: - Anticipated oral LD50 between 2000 and 5000 mg/kg; - Indication of significant effect in humans;* - Any mortality at class 4;* - Significant clinical signs at class 4;* - Indications from other studies.* *If assignment to more hazardous class is not warranted.
Dermal (mg/kg)	≤ 50	> 50 ≤ 200	> 200 ≤ 1000	> 1000 ≤ 2000	
Gases (ppm)	≤ 100	> 100 ≤ 500	> 500 ≤ 2500	> 2500 ≤ 5000	
Vapors (mg/l)	≤ 0.5	> 0.5 ≤ 2.0	> 2.0 ≤ 10	> 10 ≤ 20	
Dust & mists (mg/l)	≤ 0.05	> 0.05 ≤ 0.5	> 0.5 ≤ 1.0	> 1.0 ≤ 5	

Figure 4.11

CUTE ORAL TOXICITY - Annex 1

	Category 1	Category 2	Category 3	Category 4	Category 5
D ₅₀	£ 5 mg/kg	> 5 < 50 mg/kg	³ 50 < 300 mg/kg	³ 300 < 2000 mg/kg	³ 2000 < 5000 mg/kg

Pictogram					No symbol
Signal word	Danger	Danger	Danger	Warning	Warning
Hazard statement	Fatal if swallowed	Fatal if swallowed	Toxic if swallowed	Harmful if swallowed	May be harmful if swallowed

Table 3.9 Skin Corrosion/Irritation

Skin Corrosion Category 1			Skin Irritation Category 2	Mild Skin Irritation Category 3
Destruction of dermal tissue: visible necrosis in at least one animal			Reversible adverse effects in dermal tissue	Reversible adverse effects in dermal tissue
Subcategory 1A Exposure < 3 min. Observation < 1hr,	Subcategory 1B Exposure < 1hr. Observation < 14 days	Subcategory 1C Exposure < 4 hrs. Observation < 14 days	Draize score: $\geq 2.3 < 4.0$ or persistent inflammation	Draize score: $\geq 1.5 < 2.3$

Table 3.10 Eye Effects

Category 1 Serious eye damage	Category 2 Eye Irritation	
Irreversible damage 21 days after exposure Draize score: Corneal opacity ≥ 3 Iritis > 1.5	Reversible adverse effects on cornea, iris, conjunctiva Draize score: Corneal opacity ≥ 1 Iritis > 1 Redness ≥ 2 Chemosis ≥ 2	
	Irritant Subcategory 2A Reversible in 21 days	Mild Irritant Subcategory 2B Reversible in 7 days

Figure 4.9

GHS Pictograms and Hazard Classes		
		
▪ Oxidizers	▪ Flammables ▪ Self Reactives ▪ Pyrophorics ▪ Self-Heating ▪ Emits Flammable Gas ▪ Organic Peroxides	▪ Explosives ▪ Self Reactives ▪ Organic Peroxides

		
Acute toxicity (severe)	Corrosives	Gases Under Pressure
		
- Carcinogen - Respiratory Sensitizer - Reproductive Toxicity - Target Organ Toxicity - Mutagenicity - Aspiration Toxicity	Environmental Toxicity	- Irritant - Dermal Sensitizer - Acute toxicity (harmful) - Narcotic Effects - Respiratory Tract - Irritation

The information appearing in this document is based upon data obtained from raw material manufacturers and/or recognized technical sources. While this information is believed to be correct, TEC-GUARD makes no representations as to its accuracy or sufficiency, usage or the hazards connected with the use of this material. Since this product may be applied under conditions unfamiliar to us or beyond our control, we claim no responsibility for the results of its use, and users are responsible for the verification of this information under their own operating conditions to determine whether the product is suitable for their particular purposes, and these users assume all risks of their use, handling, and disposal of the product. This information relates only to the product designated above and does not relate to its use in combination with any other process.

TEC-GUARD Revision

Date: 06/22/2026