

TEC-GUARD

TEC-GUARD®

PGA

PETRO GEL AMBER

RETENTION
ASSEMBLY/LUBRICANT
FOR USE AS AN ASSEMBLY AID
NO EXPIRATION DATE REQUIRED

WARNING: MAY CAUSE SKIN AND EYE
IRRITATION. AVOID CONTACT WITH EYES
AND PROLONGED OR REPEATED CONTACT
WITH SKIN. IF SWALLOWED, DO NOT
INDUCE VOMITING. CALL A PHYSICIAN OR
POISON CONTROL CENTER FOR
INSTRUCTIONS. SEE SAFETY DATA SHEET
(SDS) FOR ADDITIONAL INFORMATION.
KEEP OUT OF REACH OF CHILDREN.

MADE IN THE U.S.A.
NET WT. 10 OZ.

PGA

PETRO GEL AMBER

RETENTION ASSEMBLY/LUBRICANT

TEC-GUARD® PGA PETRO GEL AMBER is a mixture of petroleum waxes and highly refined oils, formulated for a variety of automotive assembly type applications.

TEC-GUARD® PGA PETRO GEL AMBER is specifically designed to be used as an assembly aid for engine and transmission parts. Can be used in the automotive and industrial markets.

PRODUCT SPECIFICATIONS

Properties	Test	Minimum	Typical	Maximum
Melting Point	ASTM D127	110° F (43°C)	145° F (63°C)	-
Flash Point	ASTM D92	400° F (204°C)	477° F (247°C)	-
Penetration, 77° F	ASTM D937	151	180	210
Color	Amber			

- Low Melting Temperature
- Made with highly refined oils

Always consult your owner's manual for specific recommendations. DON'T POLLUTE. CONSERVE RESOURCES. RETURN CONTAINERS TO APPROVED COLLECTION CENTERS.

TEC-GUARD

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • www.tec-guard.com