

TEC-GUARD®

ARMOR

TEC-GUARD FULL SYNTHETIC
PASSENGER CAR MOTOR OIL



- Low viscosity, for gasoline engines
- Excellent thermal and oxidation stability
- Excellent low temperature capabilities

TEC-GUARD® Armor Full Synthetic 0W-40 is a full-synthetic gasoline engine oil formulated to provide outstanding anti-wear protection, high-temperature oxidation resistance and cold-flow properties. Fulfills the latest and most stringent domestic performance specifications. Fuel efficient and emissions-system compliant.

Meets or exceeds the following performance requirements and industry specifications:
API SP, API SN PLUS, SN, SM. Always consult your owner's manual for specific recommendations.

Test Method		Test Method	
Viscosity 100°C, cSt	15.2	Flash Point °C (°F)	228 (442)
Viscosity @ 40° C, cSt	87.5	Fire Point °C (°F)	244 (471)
Viscosity Index	184	Pour Point °C (°F)	-50 (-58)
Cold Crank Simulator, cP	5119 (-35)	NOCAK (% wt loss)	10.9%
Specific Gravity (g/ml)	0.8413	Four Ball Wear (75°C, 1200 rpm, 40 kg, 1 hr)	0.45
Density (lb/gal)	7.005	Total Base Number	8.0
Color	L3.5	HTHS (cP)	4.0

Always consult your owner's manual for specific recommendations. DON'T POLLUTE. CONSERVE RESOURCES. RETURN USED OIL TO APPROVED COLLECTION CENTERS.

TEC-GUARD®

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • www.tec-guard.com