

TEC-GUARD®

ARMOR

TEC-GUARD FULL SYNTHETIC
PASSENGER CAR MOTOR OILS



TEC-GUARD® Armor Full Synthetic 5W-20 is an advanced synthetic engine oil designed to prevent deposits and sludge build up and enable longer engine life. It is excellent at providing oxidation control, protect engines against low speed pre-ignition (LSPI) in turbo-charged gasoline direct injection engines (TGDI) and backward compatible with earlier API/ ILSAC performance levels.

Meets or exceeds the following performance requirements and industry specifications: FORD® WSS-M2C945-A, FORD® WSS-M2C945-B1, FORD® WSS-M2C930-A, FORD® WSS-M2C-960-A1, ILSAC GF-6, ILSAC GF-5, ILSAC GF-4, ILSAC GF-3, API SN PLUS, API SN, GM® 6094M, CHRYSLER® MS-6395. Always consult your owner's manual for specific recommendations.

- Increases fuel economy
- Excellent overall lubrication and wear protection performance for all driving styles
- Outstanding thermal and oxidation stability
- Outstanding performance during the maximum oil change interval recommended in a vehicle's owner's manual

Test Method		Product Numbers	
NOVACK Volatility	<13%	Bulk	10425204905W20
ASTM D93 - Flash Point, °C	230	Drum	10425214905W20
ASTM D97 - Pour Point, °C	-42	Pail	10425244905W20
ASTM D445 - Viscosity @ 40° C, cST	49.6	Tote	10425204905W20
ASTM D445 - Viscosity @ 100° C, cST	8.25	4/1 Gallon	10425114905W20
ASTM D2270 - Viscosity Index	162	12/1 Quart	10425264905W20
ASTM D896 - TBN	7.3		

Always consult your owner's manual for specific recommendations. DON'T POLLUTE. CONSERVE RESOURCES. RETURN USED OIL TO APPROVED COLLECTION CENTERS.

TEC-GUARD®

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • www.tec-guard.com