

TEC-GUARD®

ARMOR

TEC-GUARD SYNTHETIC BLEND FULL SYNTHETIC
PASSENGER CAR MOTOR OILS

TEC-GUARD® Armor Full Synthetic 5W-30 is an advanced synthetic engine oil designed to maximize engine protection, prevent deposits and enhance fuel economy. It is backward compatible with earlier API/ILSAC performance levels.

Meets or exceeds the following performance requirements and industry specifications: FORD® WSS-M2C929-A, FORD® WSS-M2C946-A, FORD® WSS-M2C946-B1, FORD® WSS-M2C-961-A1, ILSAC GF-6, ILSAC GF-5, ILSAC GF-4, ILSAC GF-3, API SN PLUS, API SN, ACEA A1/B1, ACEA A5/B5-16, GM® 6094M, GM® 4718M, CHRYSLER® MS-6395, HONDA®/ACURA® HTO-06. Always consult your owner's manual for specific recommendations.

Test Method		Product Numbers	
NOVACK Volatility	<13%	Bulk	10425204905W30
ASTM D93 - Flash Point, °C	210	Drum	10425214905W30
ASTM D97 - Pour Point, °C	-48	Pail	10425244905W30
ASTM D445 - Viscosity @ 40° C, cST	63.1	Tote	10425204905W30
ASTM D445 - Viscosity @ 100° C, cST	11.2	4/1 Gallon	10425114905W30
ASTM D2270 - Viscosity Index	175	12/1 Quart	10425264905W20
ASTM D896 - TBN	7.3		

- Increases fuel economy
- Excellent piston cleanliness and engine sludge control
- Provides emission systems protection

Always consult your owner's manual for specific recommendations. DON'T POLLUTE. CONSERVE RESOURCES. RETURN USED OIL TO APPROVED COLLECTION CENTERS.

TEC-GUARD

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • www.tec-guard.com