

TEC-GUARD®

ARMOR

TEC-GUARD SYNTHETIC BLEND HIGH MILEAGE PASSENGER CAR MOTOR OILS



- Extended Drain Capabilities
- Resists Thermal Breakdown
- Engine Cleanliness
- Maximizes Power Output
- Extra Protection for Emission Systems
- Reduces Oil Consumption

TEC-GUARD® Armor High Mileage motor oils are superior synthetic blend oils formulated to provide long engine life and premium protection for vehicles with more than 75,000 miles.

They meet modern engine performance demands for improved resistance to oxidation, deposit control, wear protection, prevent oil leakage, helps remove built up of sludge deposits and are backward compatible with earlier API/ILSAC performance levels.

Test Method	5W-20	5W-30	10W-30
ASTM D445 - Viscosity @ 40°C, cSt	49.21	63	68.2
ASTM D445 - Viscosity @ 100°C, cSt	8.59	10.5	10.5
ASTM D2270 - Viscosity Index	153	158	141
ASTM D97 - Pour Point, °C	-48	-48	-42
ASTM D92 - Flash Point, °C	244	230	232
NOACK Volatility	<13%	<13%	<12%
API SN PLUS RC, API SN PLUS, API SN RC, API SN, API SM, API SL, API SJ	XX		X
ILSAC GF-6, ILSAC GF-5, ILSAC GF-4	X	X	X
Ford WSS-M2C945-A, Ford WSS-M2C945-B1	X		
Ford WSS-M2C946-A, Ford WSS-M2C946-B1		X	
Ford WSS-M2C929-A		X	
Ford WSS-M2C930-A	X		
GM 6094M, Chrysler MS-6395	X	X	X

Always consult your owner's manual for specific recommendations. DON'T POLLUTE. CONSERVE RESOURCES. RETURN USED OIL TO APPROVED COLLECTION CENTERS.

TEC-GUARD

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • www.tec-guard.com