



ARMOR

TEC-GUARD SYNTHETIC BLEND MOTOR OILS



TEC-GUARD® Armor Synthetic Blend 20W-50 Motor Oil is made with enhanced wear protection and outstanding resistance to thermal breakdown at operating temperatures.

TEC-GUARD® Armor Synthetic Blend 20W-50 Motor Oil also meets API Service Categories SN, SM, SL etc. specifications.

TEC-GUARD® Armor Synthetic Blend 20W-50 Motor Oil meets or exceeds the North American warranty requirements for U.S., European and Japanese cars and light trucks and small power equipment, generators, and off-road equipment with gasoline and gasoline turbo-charged engines where API SN, SM, SL, SJ etc. oils are specified.

- Extremely high temperature protection
- Protection against deposits and acids, which result in a cleaner running engine
- Fully compatible with conventional engine oils.

Physical Characteristics

Viscosity Grade		20W-50
API Service Category		SN
ILSAC		-
Density kg/cm ³	ASTM D4052	879
Flash Point °C	ASTM D93	204
Pour Point °C	ASTM D97	-29
Viscosity @40°C	ASTM D445	160.8
Viscosity @100°C	ASTM D445	17.7
Viscosity Index	ASTM D2270	122
CCS Viscosity @-15°C	ASTM D5293	7,520
MRV Viscosity @-20°C	ASTM D4684	19,900