

TEC-GUARD®

ARMOR

TEC-GUARD SYNTHETIC BLEND PASSENGER CAR MOTOR OILS



TEC-GUARD® Armor Synthetic Blend Passenger Car Motor Oils are premium quality motor oils formulated from selected superior base oils and advanced additive technology, providing the highest levels of equipment protection available. They are the excellent choice for passenger cars, light trucks, powerboats, motorcycles, and other stationary and mobile equipment. They exceed the performance requirements of API's Resource Conserving "SN Plus" and car manufacturers' ILSAC GF-6 classification as well as all prior classifications providing the latest technology in fuel economy standards while also maintaining best in class wear control, cleanliness, protection against sludge, and oxidation control.

- Excellent Fuel Economy
- Advanced varnish & sludge protection
- Excellent cold-crinking capabilities
- Excellent volatility for low oil consumption
- Excellent anti-wear, anti-foaming, bearing corrosion and anti-rust protection
- Excellent protection from deposits at all operating temperatures

Test Method	5W-20	5W-30	10W-30
ASTM D445 - Viscosity @ 40°C, cSt	49.6	60.1	63.1
ASTM D445 - Viscosity @ 100°C, cSt	8.25	10.2	10.2
ASTM D2270 - Viscosity Index	162	158	150
ASTM D97 - Pour Point, °C	-42	-48	-46
ASTM D92 - Flash Point, °C	230	234	238
NOACK Volatility	<13%	<13%	<15%
API SN Resource Conserving, API SN, PLUS	X	X	X
API SN Resource Conserving, API SN, API SM	X	X	X
API SL, API SJ	X	X	X
ILSAC GF-6, ILSAC GF-5, ILSAC GF-4	X	X	X
Ford WSS-M2C945-A, Ford WSS-M2C945-B1	X		
Ford WSS-M2C946-A, Ford WSS-M2C946-B1		X	
Ford WSS-M2C929-A		X	
Ford WSS-M2C930-A	X		
Ford WSS-M2C-960-A1	X		
Ford WSS-M2C-961-A1		X	
GM 6094M, Chrysler MS-6395	X	X	X

Always consult your owner's manual for specific recommendations. DON'T POLLUTE. CONSERVE RESOURCES. RETURN USED OIL TO APPROVED COLLECTION CENTERS.

TEC-GUARD

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • www.tec-guard.com