



ARMOR

TEC-GUARD SYNTHETIC BLEND PASSENGER CAR MOTOR OILS



TEC-GUARD® Armor Synthetic Blend 5W-20 is a synthetic blend engine oil that offers excellent oxidation stability, additional high temperature protection, better cold weather properties than conventional motor oils and it is backward compatible with earlier API/ILSAC performance levels.

TEC-GUARD® Armor Synthetic Blend 5W-20 meets or exceeds the following performance requirements and industry specifications: FORD® WSS-M2C-960-A1, FORD® WSS-M2C930-A, FORD® WSS-M2C945-B1, FORD® WSS-M2C945-A, ILSAC GF-6, ILSAC GF-5, ILSAC GF-4, ILSAC GF-3, API SN PLUS, API SN, GM® 6094M, CHRYSLER® MS-6395. Always consult your owner's manual for specific recommendations.

- Outstanding wear protection under a wide variety of operating conditions
- Helps extend engine life
- Compatible with leading motor oils
- Superior cold-cranking capabilities

Test Method		Product Numbers	
NOVACK Volatility	<13%	Bulk	10425204805W20
ASTM D93 - Flash Point, °C	230	Drum	10425214805W20
ASTM D97 - Pour Point, °C	-42	Pail	10425244805W20
ASTM D445 - Viscosity @ 40° C, cST	49.6	Tote	10425204805W20
ASTM D445 - Viscosity @ 100° C, cST	8.2	4/1 Gallon	10425114805W20
ASTM D2270 - Viscosity Index	162	12/1 Quart	10425264805W20