



# ARMOR

TEC-GUARD SYNTHETIC BLEND PASSENGER CAR MOTOR OILS



TEC-GUARD® Armor Synthetic Blend 5W-30 is a synthetic blend engine oil that offers excellent oxidation stability, increases your engine's fuel economy, protects against deposits at all temperatures and it is backward compatible with earlier API/ILSAC performance levels.

TEC-GUARD® Armor Synthetic Blend 5W-30 meets or exceeds the following performance requirements and industry specifications:

ILSAC GF-6, ILSAC GF-5, ILSAC GF-4, ILSAC GF-3, API SN PLUS, API SN, WSS-M2C-960-A1, FORD® WSS-M2C946-A, FORD® WSS-M2C946-B1, FORD® WSS-M2C929-A, GM® 6094M, CHRYSLER® MS-6395. Always consult your owner's manual for specific recommendations.

| Test Method                         |      | Product Numbers |                |
|-------------------------------------|------|-----------------|----------------|
| NOVACK Volatility                   | <13% | Bulk            | 10425204805W30 |
| ASTM D93 - Flash Point, °C          | 234  | Drum            | 10425214805W30 |
| ASTM D97 - Pour Point, °C           | -48  | Pail            | 10425244805W30 |
| ASTM D445 - Viscosity @ 40° C, cST  | 60.1 | Tote            | 10425204805W30 |
| ASTM D445 - Viscosity @ 100° C, cST | 10.2 | 4/1 Gallon      | 1042511805W30  |
| ASTM D2270 - Viscosity Index        | 158  | 12/1 Quart      | 10425264805W30 |

- Excellent thermal oxidation control
- Industry leading high temperature deposit control
- Superior cold-cranking capabilities
- Enhanced anti-wear, anti-foam, bearing corrosion
- and anti-rust protection

TEC-GUARD

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • [www.tec-guard.com](http://www.tec-guard.com)