

TEC-GUARD

DEFEND

TEC-GUARD DEFEND SCREW MACHINING OIL

TEC-GUARD® DEFEND Screw Machining Oil CUT-SMO-32 is a complex unique blend of proprietary Basestocks and high end paraffinic basestocks. Included in this unique blend is advanced ester technology not found in typical metalworking manufacturing oils. The ester additive package allows CUT-SMO-32 to perform all machining operations such as turning, milling, cutting, screw machining and hobbing without the need to alter the oil for the more difficult operations. The beauty of CUT-SMO-32 is that the viscosity can be adjusted based off customer's needs and specific operations without sacrificing the ester based additive package ability to perform. **TEC-GUARD® DEFEND Screw Machining Oil CUT-SMO-32** can be used on all metals without the fear or staining the "yellow metals."

TEC-GUARD DEFEND SCREW MACHINING OIL

BENEFITS:

- LOW ODOR
- HIGH OPERATOR ACCEPTANCE
- EASY TO CLEAN
- EXCEPTIONAL TOOL LIFE
- IMPROVED PRODUCTIVITY



Test Method	CUT-SMO-32
Viscosity @ 40°C, cSt SUS	36-43
Flash Point, °F	370
Color	CLEAR AMBER

DON'T POLLUTE. CONSERVE RESOURCES. RETURN USED OIL TO APPROVED COLLECTION CENTERS.

TEC-GUARD

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • www.tec-guard.com