

TEC-GUARD

EXTREME

TEC-GUARD EXTREME HIGH PERFORMANCE FULL SYNTHETIC GEAR OILS

TEC-GUARD® Extreme High Performance Gear Oils are premium quality limited slip gear oils blended from synthetic base oils and an advanced additive package, they are designed to provide protection under severe operating conditions, reduce operating costs, and improve fuel economy.

TEC-GUARD® Extreme Full Synthetic Limited Slip 75W-140 Gear Oil meets the requirements of API GL-5, API MT-1, MIL-PRF-2105E and MIL-PRF-2105D for use in passenger cars, light-duty trucks, axles of heavy-duty trucks, off-road equipment, tractors and outboard motors with limited-slip differentials, manual transmissions and final drives. Meets Mack® GO-J, GO-H, GO-G, MIL-L-2105D, ArvinMeritor® O76-E requirements, always consult your owner's manual for specific recommendations.

Test Method		Product Numbers	
Viscosity: cSt @ 40°C	194.75	Bulk	10421203575140
Viscosity: cSt @ 100°C	27.3	Drum	10421213575140
Viscosity Index	178	Pail	10419243575140
Pour Point, 60°F	-38	Keg	
Flash Point, (COC), °F	450	Tote	10421203575140
API Gravity @ 60°F	33.9	Gallon	10421123575140
Specific Gravity, 60°F	0.856		

- Enhanced Frictional Properties
- Resistant To Foaming
- Potential Extended Oil Drain/Service Intervals

TEC-GUARD

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • www.tec-guard.com