

# TEC-GUARD

## EXTREME

### TEC-GUARD EXTREME HIGH PERFORMANCE FULL SYNTHETIC GEAR OILS

TEC-GUARD® Extreme High Performance Gear Oils are premium quality limited slip gear oils blended from synthetic base oils and an advanced additive package, they are designed to provide protection under severe operating conditions, reduce operating costs, and improve fuel economy.

TEC-GUARD® Extreme Full Synthetic Limited Slip 75W-90 Gear Oil meets the requirements of API GL-5, API MT-1, MIL-PRF-2105E and MIL-PRF-2105D for use in passenger cars, light-duty trucks, axles of heavy-duty trucks, off-road equipment, tractors and outboard motors with limited-slip differentials, manual transmissions and final drives. Meets Mack® GO-J, GO-H, GO-G, MIL-L-2105D, ArvinMeritor® O76-E requirements, always consult your owner's manual for specific recommendations.



- Enhanced Frictional Properties
- Resistant To Foaming
- Potential Extended Oil Drain/Service Intervals

| Test Method                         |      | Product Numbers |                |
|-------------------------------------|------|-----------------|----------------|
| Specific Gravity @ 60°F             | .875 | Bulk            | 10421205375W90 |
| ASTM D92 - Flash Point, °C          | 150  | Drum            | 10421212575W90 |
| ASTM D5949 - Pour Point, °C         | -48  | Pail            | 10419246375W90 |
| ASTM D445 - Viscosity @ 40° C, cST  | 126  | Keg             |                |
| ASTM D445 - Viscosity @ 100° C, cST | 17.3 | Tote            | 10421205375W90 |
| ASTM D2270 - Viscosity Index        | 151  |                 |                |

TEC-GUARD

400 S 14 Ave • Eldridge, IA 52748 • 800-522-1150 • [www.tec-guard.com](http://www.tec-guard.com)